RECEIVED CENTRAL FAX CENTER

p.1

JUL 1 6 2004

# IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the application of:

Alf Hammes

Docket: ZOU-1999DE507

Serial Number: 10/070,071

Group Art Unit: 1623

Filed: 06/27/2002

Examiner: Everett White

For: Low Viscous Cellulose Ethers That Flocculate in Hot Water, Method for The

ROBERTS & ROBERTS, LLP

Production Thereof and Their Use

# NOTICE: THIS APPLICATION IS UNDER FINAL REJECTION

### FAX COVER SHEET

TO:

Commissioner for Patents

P.O. Box 1450

Alexandria, VA 22313-1450

FAX NO.: (703) 872-9306

FROM:

Richard S. Roberts

Reg. No. 27941

P.O. Box 484

Princeton, New Jersey 08542

(609) 921-3500

DATE:

July 16, 2004

KINDLY DIRECT THIS COMMUNICATION TO:

**EXAMINER: Everett White** 

GROUP : 1623

NO. OF PAGES SENT INCLUDING THIS COVER SHEET: 6

If all pages are not received, please call (609) 921-3500.

RECEIVED
GENTRAL FAX CENTER

JUL 1 6 2004

## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the application of:

Alf Hammes

Docket: ZOU-1999DE507

Serial Number: 10/070,071

Group Art Unit: 1623

Filed: 06/27/2002

Examiner: Everett White

For: Low Viscous Cellulose Ethers That Flocculate in Hot Water, Method for The

Production Thereof and Their Use

## NOTICE: THIS APPLICATION IS UNDER FINAL REJECTION

### RESPONSE TO OFFICE ACTION

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

Sir:

In response to the Office Action mailed April 16, 2004, please consider the following remarks:

#### **REMARKS**

The examiner has rejected claims 1-8, 10, and 11 under 35 U.S.C. 103 over Traill et al. in view of Savage. It is respectfully urged that this ground of rejection is not well taken.

The present invention relates to a process for forming low-viscosity, hot water-coagulable cellulose ethers. The application claims the depolymerization of such cellulose ethers by hydrolytic degradation. In particular the invention claims: A process for the depolymerization of hot water-coagulable cellulose ethers by hydrolytic degradation by means of acids, wherein the degradation is carried out at a temperature above the cloud point of the cellulose ether as concentrated aqueous slurry, and in addition at least one oxidizing agent is added to the concentrated aqueous slurry in an amount of between 0.05